



TWX37ST

LASER PROJECTOR



01

APPEARANCE

Model : TWX37ST



02

OPTICAL SPECIFICATIONS

Brightness	4500 ISO Lumen (3700 ANSI Lumen)
Display Technology	3LCD
Contract Ratio	15000:1 (with IRIS&ECO mode)
Resolution	XGA (1024x768)
Lamp Consumption	Philips :218W
Noise	ECO: Max 34.9dB, Normal: 38.9dB
Lamp Life Time	5000H(Normal) /10000H(ECO)
Display Panel	3x0.63"
Aspect Ratio	4:3 (Standard)/16:9(Compatible)

03

PROJECTION LENS

Focus	Manual
Throw Ratio	0.45 : 1(87"@0.75m)
F	F=1.7
f	f= 6.09mm
Screen Size	0.455~0.943m(50"~100")

04

GENERIC SPECIFICATIONS

Speaker	1*10W
Scranning Frequency	Hsync Frequency 15~100KHz / Vsync Frequency 48~85Hz
Computer Signal Input	PC, VGA, SVGA, XGA, SXGA, WXGA, UXGA, WUXGA, Mac
Video Compatibility	PAL, SECAM, NTSC 4.43, PAL-M, PAL-N, 480i, 480p, 576i, 576p, 720p, 1080p and 1080i
Power Requirements	100~240V@ 50/60Hz
Power Consumption	270W (ECO:<0.5W)
ECO Standby Mode Power Consumption	<0.5W
Network Standby Mode Power Consumption	<3W
Keystone Correction	V: $\pm 30^\circ$ (auto+manual), H: $\pm 15^\circ$ (manual), Pincushion/Barrel Correction, Corner Keystone
OSD(Languages)	26 languages: English, German, French, Italian, Spanish, Polish, Swedish, Dutch ,Portugese, Japanese, Simplified Chinese, Traditional Chinese, Korea, Russian, Arabic, Turkish, Finnish, Norwegian, Danish, Indonesian, Hungarian, Czech, Kazak, Vietnamese,Thai, Farsi
Input Terminals	VGA x 2 , Audio in (mini jack , 3.5mm) x 1 , YCbCr/Component x 1 (share with VGA in 1) , Video x 1 , Audio in (L/R) -RCA x 2 , S-video x 1 (share with VGA in 1) , HDMI x 2 (tương thích với MHL) , USB-A x 1 (hỗ trợ MemoryViewer và Wifi Dongle) , USB-Bx 1 (Display) , RJ-45 x 1 (Display)
Output Terminals	VGA x 1 (Share với VGA IN 2) , Audio out (mini-jack , 3.5mm) x 1
Other Terminals	RS-232x1, RJ45 x 1 (for control) , USB-Bx 1 (for up-grade) , Remote Control Receiver x 1

05

MECHANICAL SPECIFICATIONS

Power Supply	AC 100-240V ~ 50-60 Hz
Net.Weight (KG)	4 kg
Max Dimensions (Wxhxdmm)	347(W) x 341(D) x 142(H) mm

06

STANDARD ACCESSORIES

Standard

Power cord, VGA cable, Remote control, Service Card, QSG (for Projector)

07

PROJECTION DISTANCE

Model	Screen Size	4:3	16:9
		Distance	Distance
TWX37ST	50°	0.455m	0.498m
	60°	0.552m	0.605m
	70°	0.65m	0.711m
	80°	0.748m	0.817m
	90°	0.845m	0.924m
	100°	0.943m	1.03m

TWT APPLIED TECHNOLOGY AND SERVICES PTE LTD

TWT reserves the right to change products' dimensions and specifications without notice
 TWT APPLIED TECHNOLOGY AND SERVICES PTE LTD reserves the ultimate right to the interpretation of this catalogue.
 ADDRESS : 71 BUKIT BATOK CRESCENT #09-04 PRESTIGE CENTRE SINGAPORE 658071
 TEL : +65 9798 4332

